

AUTOANCHOR 560 WINDLASS CONTROL AND RODE COUNTER

AutoAnchor 560 controls the windlass from the helm station and shows at a glance how much anchor rode is deployed. Fits any windlass.

Features

- “One touch” automatic function deploys and retrieves a preset length of anchor rode making anchoring easier and safer
- Docking alarm and pre-set stopping point help protect the boat during anchor retrieval
- Adjustable backlighting ensures clear night operation
- Choice of feet, metres or fathoms rode measurement
- Safety lock reduces unwanted windlass operation
- Easy installation and set up
- Plug and play sensor installation
- Works with rope/chain or all-chain rode.
- Use with DC, AC and hydraulic windlasses
- Logs windlass operating hours for maintenance
- Inbuilt diagnostics for installation troubleshooting
- Install up to 2 units or combine with the AA150, AA710 or AA300 series for multiple stations on the boat
- Weather cover protects the console unit
- Console colour choice – black or grey



AA560 Kit Includes: 1 console unit, 1 sensor, 1 magnet, load sensing connectors, installation and operation instructions

Technical Specifications

Power Supply	12 or 24V DC
Maximum Voltage	30V DC
Current Consumption	70mA
Output Maximum Current Draw	12V DC: 4A 24V DC: 4A
Output Minimum Current Draw	12V DC: 10mA 24V DC: 20mA When connecting to a solid state switching or other low current windlass drive, a PLC or AC variable frequency drive, a dummy resistor load (Part #9515) may be required.
IP Rating	IP67 from the front provided the unit is mounted so the back is protected from moisture.
Operating Temperature Range	23°F to 140°F (-5°C to 60°C)
Sensor	Compatible with all AutoAnchor sensors, reed switches and some proximity switches.
Rode – Chain Only	Stainless or galvanised steel.
Rode – Rope and Chain	Must have a minimum of 10ft (3m) of chain. Chain must be galvanised steel. Rope should be a good quality nylon anchor rope. Type 66 or equivalent.
EMC Protection/CE	EN60945
For DC windlasses a dual direction solenoid is required.	

Kiwi Yachting reserves the right to amend product specifications without notice.